

HXPA9081G Power Amplifier

1. Description

ID	Items	Specifications
1-1	Type	Power Amplifier
1-2	Frequency Range	0.3 ~ 18GHz
1-3	Gain	$\geq 16\text{dB}$
1-4	Gain Flatness	$\leq \pm 1.0\text{dB}$
1-5	Output 1dB Compression Point(P1dB)	$\geq 27\text{dBm}$
1-6	Saturated Output Power(Psat)	/
1-7	Input VSWR	≤ 2.5
1-8	Isolation S12	$\geq 20\text{dB}$
1-9	Spurious	$\leq -60\text{dBc}$
1-10	Noise Figure	5.0dB Typical
1-11	Impedance	50 Ω
1-12	Input/Output Connectors	SMA-F
1-13	DC Power Supply	+12V/ $\leq 400\text{mA}$

2. Absolute Maximum Ratings


ID	Parameter	Rating
2-1	Operating Voltage	12 ~ 12.5V
2-2	RF Input Power	$\leq 10\text{dBm}$
2-3	Include voltage protection, current protection and temperature protection	

3. Environmental Specifications

ID	Items	Specifications
3-1	Operational Temperature	-40°C ~ +70°C
3-2	Storage Temperature	-55°C ~ +85°C

4. Outline Drawing

ID	Items	Specifications
4-1	Outline Drawing	Unit: mm
Tolerances: $\pm 0.1\text{mm}$		



4-2	Material	Aluminum
4-3	Finished	Natural Color
4-4	Weight	50g

NOTE: ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.